



IMG_3238.jpeg





IMG_3240.jpeg



IMG_3241.jpeg















































MANUFACTURED BY / FABRIQUÉ PAR : K-TRAIL

DATE : 02/2020

GVWR / PNBV : 4479 KG (9875 LB)

COLD INFL. PRESS. / PRESS.

GAWR (EACH AXLE) /

DE GONFL. À FROID

PNBE (CHAQUE ESSIEU) TIRE / PNEU

RIM / JANTE

KPA (PSI / LPC)

2359 KG (5200 LB)

ST225/75/R15 (D)

15 X 6 J

448 KPA (65 PSI) SINGLE

THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / CE VÉHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE

V.I.N./N.I.V. 2RYKBP29LM025179

TYPE : TRA / REM

DKO20-10



TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed 2,939 kg ou 6,480 lbs.
Le poids du chargement ne doit jamais dépasser

TIRE /
PNEU

SIZE /
DIMENSIONS

COLD TIRE PRESS. / PRESS.
DES PNEUS À FROID

FR/AV

ST225/75/R15 (D)

448 KPA (65 PSI)

INT/INT

NONE/AUCUN

RR/AR

ST225/75/R15 (D)

448 KPA (65 PSI)

SPARE/DE SECOURS

NONE/AUCUN

SEE OWNER'S
MANUAL FOR
ADDITIONAL
INFORMATION
VOIR LE MANUEL
DE L'USAGER
POUR PLUS DE
RENSEIGNEMENTS

2RYKBP29LM025179