



Entrepreneur

MANUFACTURED BY / FABRIQUÉ PAR : K-TRAIL
DATE : 10/2022 GVWR / PNEV : 1297 KG (2850 LB) COLD INFL. PRESS. / PRESS. DE GONFL. À FROID
GAWR (EACH AXLE) / PNEB (CHAQUE ESSIEU) TIRE / PNEU RIM / JANTE KPA (PSI / LPC)
1588 KG (3500 LB) ST175/80R13 (D) 13 X 5J 345 KPA (50 PSI) SINGLE
THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / CE VEHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES VEHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE
V.I.N./N.I.V. **2RYKBAD20PM036952** TYPE : TRA / REM 68123-VTT-T

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT
The weight of cargo should never exceed 951 kg or 2,096 lbs.
Le poids du chargement ne doit jamais dépasser 951 kg ou 2,096 lbs.
SEE DRIVER'S MANUAL FOR ADDITIONAL INFORMATION. / VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS.
2RYKBAD20PM036952

TIRE / PNEU	SIZE / DIMENSIONS	COLD TIRE PRESS. / PRESS. DES PNEUS À FROID	SEE DRIVER'S MANUAL FOR ADDITIONAL INFORMATION. / VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
FR/AV	ST175/80R13 (D)	345 KPA (50 PSI)	
INT/INT.	NONE/AUCUN		
DIR/AR	ST175/80R13 (D)	345 KPA (50 PSI)	
SPARE/DE SECOURS	NONE/AUCUN		

IMG_2863.jpeg



IMG_2864.jpeg



IMG_2865.jpeg



IMG_2866.jpeg



IMG_2867.jpeg



IMG_2868.jpeg



IMG_2869.jpeg



IMG_2870.jpeg



IMG_2871.jpeg



IMG_2872.jpeg



IMG_2873.jpeg



IMG_2874.jpeg



IMG_2875.jpeg



IMG_2876.jpeg



IMG_2877.jpeg



IMG_2878.jpeg



IMG_2877.jpeg

