

































MANUFACTURED BY / FABRIQUE PAR: FOREST RIVER, INC. DATE: 08/23/2024 ACAT39FKTS
GYMHPNBV: 4990 KG (11000 LB)
GAWR(EACH AXLE) / PNBE(CHAUQUE ES SIEU): 2313 KG (5100 LB)
TIRES/PNEU: ST225/75R15/E RIMSQUANTE: 15X6.0JJ
COLD INFL. PRESS./PRESS. DE GONFL. À FROID: 552 KPA (80 PSI/LPC)

THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE.

CE VÉHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION.

V.I.N.N.I.V.: 5ZT2CA4B25X032913

TYPE/TYPE: TR/REM

COUPLER SIZE/TAILLE DU COUPLEUR: 2-5/16"

The combined weight of cargo should never exceed 482 kg or 1063 lbs.

TIRE	SIZE	COLD TIRE PRESSURE
FRONT	ST225/75R15/E	80 PSI / 552 KPA
REAR	ST225/75R15/E	80 PSI / 552 KPA
SPARE	ST225/75R15/E	80 PSI / 552 KPA

Le poids du chargement ne doit jamais dépasser
482 kg ou 1063 lb.

PNEU	DIMENSIONS	PRESSIION DES PNEUS À FROID	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
AVANT	ST225/75R15/E	80 LB/PO2 / 552 KPA	
ARRIÈRE	ST225/75R15/E	80 LB/PO2 / 552 KPA	
DE SECOURS	ST225/75R15/E	80 LB/PO2 / 552 KPA	













IMG_0608.jpeg





































