



IMG_4830.jpeg

















IMG_4838.jpeg



A photograph showing a close-up of a wooden deck surface. A yellow measuring tape is stretched across the deck planks, displaying markings for 54 inches, 1 foot, and 1 foot 6 inches. A rusty, bent metal bracket or piece of hardware lies on the deck near the tape. The deck shows signs of wear, including splintered wood and patches of white material, possibly snow or paint. A large, semi-transparent watermark reading 'Montreal' is overlaid diagonally across the image.

A photograph showing a rusty metal bracket and a yellow strap on a wooden surface. The strap has text including 'MAGNETIC', 'S 100745', 'KGT 100745', and 'M11'. A large 'Entrepren' watermark is visible across the image.









IMG_4844.jpeg







PRESS. / PRESS.
À FROID
(LPC)

(125 PSI) DUAL

SEE SAFETY REGULATIONS IN EFFECT ON
LES EN VERTU DU RÈGLEMENT SUR LA

ON THE DATE OF MANUFACTURE SHOWN

FW30+5LHT30HR40



TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed 12,322 kg or 27,165 lbs.
Le poids du chargement ne doit jamais dépasser

TIRE / PNEU	SIZE / DIMENSIONS	COLD TIRE PRESS. / PRESS. DES PNEUS À FROID
FR/AV	ST215/75/R17.5 (H)	862 KPA (125 PSI)
INT/INT	NONE/AUCUN	
RR/AR	ST215/75/R17.5 (H)	862 KPA (125 PSI)
SPARE/DE SECOURS	NONE/AUCUN	

SEE OWNER'S
MANUAL FOR
ADDITIONAL
INFORMATION
VOIR LE MANUEL
DE L'USAGER
POUR PLUS DE
RENSEIGNEMENTS

2RYKFP27JMO18037







IMG_4851.jpeg





