









IMG_7923.jpeg





IMG_7926.jpeg







IMG_7930.jpeg



IMG_7931.jpeg









IMG_7935.jpeg



IMG_7923.jpeg



DECK SERIES

MAINTAINED BY / FABRIQUE PAR : KTRAM
 DATE : 10/2025 GVWR / PNEU : 95157 KG (35575 LB) COLD WFT. PRESS. PRESS.
 GAWG (EACH AXLE) DE QUOT. A FROID
 PMBE (CHARGE E-SEUL) TIRE / PNEU RPS / JANTE KPA (PSI / LPI)
 DATA NO (FROM LBS) 6725+27871.5 (15) 17.5 X D 182 KPA (125 PSI) CUAL
 THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE / CE VOITURE EST CONFORME A TOUTES LES NORMES QUI SONT APPLIQUEES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEICULES AUTOMOBILES DU CANADA EN TOUTES LES DATES DE SA FABRICATION
 THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE / CETTE VOITURE CONFORME A TOUTES LES NORMES FEDERALES DE SECURITE DES VEICULES AUTOMOBILES EN TOUTES LES DATES DE SA FABRICATION
 VIN/BELY 3RYKCPM2XR/M033756 TYPE / TRAITEMENT GN25+5LHT30HR40

THE WEIGHT OF LOADS EXCEEDS DRIVE DESIGN 12,644 LBS 57,875 lb
 LE POIDS DE CHARGEMENT EXCEDE LE POIDS MAXIMUM PERMIS

TIRE / PNEU	182	COLD TIRE PRESS. / PRES. TIRE FROIDE	125 PSI / 8.6 BAR
JANTE	182	GAWG / CHARGE	125 PSI / 8.6 BAR
STUD	182	STUD TORQUE / TORQUE ETUDE	125 PSI / 8.6 BAR
WHEEL	182	WHEEL TORQUE / TORQUE ROUE	125 PSI / 8.6 BAR

DDEXTOR

TORQUE SPECIFICATIONS

10 STUD HUBS
FOR BALL BEAT MOUNTED DISC-WHEELS
RECOMMENDED TORQUE DRY:
 1-18 AND 3-18 THROUGH 440-500 FT-LBS.

SPOKE WHEELS
TIGHTEN RIM NUTS ONE QUARTER TURN AT A TIME IN SEQUENCE SHOWN
RECOMMENDED TORQUE:
 200-250 FT. LBS.

HEEL-LESS CLAMP
 Heel-less clamps do not depend on a fulcrum at the bottom of the clamp to produce the force to wedge the rim. Back of clamp does not sit flat.

8 ON 275mm STUD HUBS
10 ON 285.75mm STUD HUBS
FOR HUB-PILOTED DISC-WHEELS
RECOMMENDED TORQUE DRY:
 M22 X 1.5 THREAD 450-500 FT-LBS

2-PIECE FLANGE HUB - Torque 2-piece flange nuts to 10-15 ft-lbs. Inlet sequence shows, then tighten 2-piece flange nuts to recommended torque.

www.dexter-trailer.com

