























IMG_1149.jpeg







IMG_1168.jpeg



IMG_1150.jpeg

































MFG BY / FABRIQUE PAR: GULF STEAM COACH, INC.		REFER TO TRIP PLANNER FOR MAXIMUM VEHICLE LOADING	
DATE OF MFG/FABRIQUE DATE: 01/31/24	MFG. VER. MFG. BY: N/A	DATE OF MFG/FABRIQUE: N/A	PNBY/RYNR: 1723 kg (3800)
PNBY AVANT / GAWP FRONT: N/A	PNBY TIRE: N/A	JANTE / RIMS: N/A	PRESS DE GONFL A FROID/COLD INFL PRESS: N/A
PNBY INTERM / GAWP INTERM: N/A	PNBY TIRE: N/A	JANTE / RIMS: N/A	PRESS DE GONFL A FROID/COLD INFL PRESS: N/A
PNBY ARRIERE / GAWP REAR: 1587kg (3500 LB)	PNBY TIRE: ST235/75R15D	JANTE / RIMS: 15 x 6	PRESS DE GONFL A FROID/COLD INFL PRESS: 448 kPa (65psi)
THIS VEHICLE HAS BEEN COMPLETED IN ACCORDANCE WITH THE PRIOR MANUFACTURERS' AND WHERE APPLICABLE, JAN 24 THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN THE U.S.A. IN EFFECT ON THE DATE OF MANUFACTURE. CE VEHICULE EST CONFORME A TOUTES LES NORMES DU LUS ST/1 APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN VIGUEUR A LA DATE DE SA FABRICATION			
V. / N.L.V.: 1N1G1616R6017931	Serial No. / No. de serie: 76-4-T-150RD-17931	TYPE: TRAILER	
1N1G1616R6017931		**	

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed 367 kg or 809 lbs.
Le poids du chargement ne doit jamais dépasser kg ou lbs.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
FRONT AVANT	N/A	N/A	
REAR ARRIERE	ST235/75R15D	448 kPa (65psi)	
SPARE DE SECOURS	ST235/75R15D	448 kPa (65psi)	

SN: 76-4-T-150RD-17931

RECREATIONAL VEHICLE TRAILER CARGO CARRYING CAPACITY

VIN: 1N1G1616R6017931

THE WEIGHT OF CARGO SHOULD NEVER EXCEED 368.9 kg or 809 lbs

CAUTION: A full load of water equals 13.2 kg or 29 lbs of cargo @ 1kg/L (2.3 lb/gal)



Dee Jay Trailers
(BELMONT) LTD.

Go RVing
Life's A Trip™

Hwy. #7, Havelock
www.deejaytrailers.com
1-800-900-5557

