

DATE 10/19/2021 MANUFACT

VIN/NIV 4YDTPPJ27NK411521 TYPE

UNLOADED VEHICLE WEIGHT 2123

GVWR / PNBV 2917

AWR (EACH AXLE)/PNBE(CHACQUE ESSIEU) 1588

TIRE / PNEU ST205

RIMS/JANTE 14x5.5

COLD INFL. PRESS/PRESS. DE GONFL. A FROID 448 KPA

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS AND REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DE LA CONSTRUCTION DES VEHICULES A LA DATE DE SA FABRICATION.

ALL WEIGHTS ARE APPROXIMATE.

CARGO AND PASSENGER CAPACITY 613 KG / 1351 LB	CAPACITE DE CHARGEMENT
CALCULATED WITH THE FRESH WATER TANKS FULL	CALCULEE AVEC LES RESERVOIRS D'EAU FRAICHE PLEINS
COLD 140 KG / 309 LB	FROID 140 KG / 309 LB
HOT 23 KG / 50 LB	CHAUDE 23 KG / 50 LB
AND THE WASTE WATER TANKS EMPTY	ET LES RESERVOIRS D'EAU USEE VIDES
MASS OF WASTE WATER TANKS FULL	MASSA DES RESERVOIRS D'EAU USEE PLEINS
277 KG / 611 LB	277 KG / 611 LB



















IMG_0821.jpeg





















A photograph of the interior of a boat's engine compartment. The compartment is cluttered with various mechanical parts, including a blue corrugated hose, a black fuel filter, and a black fuel line. A warning label is visible on the right side of the compartment, and a blue cap is on the top right.

A collection of mechanical parts, including a blue corrugated hose, a metal manifold, and various fittings, laid out on a wooden surface. The parts are arranged in a somewhat organized manner, with the blue hose on the left and the manifold in the center. The background is a plain wooden surface.













































FABRIQUE PAR: KEYSTONE RV COMPANY
2642 HACKBERRY DRIVE
GOSHEN, IN 46526

MODEL: PP219BH22

14680 LB
16430 LB
13500 LB
75R14D

PA 165 PSI/LPC - SINGLE

SAFETY STANDARDS IN EFFECT ON THE DATE OF
LE STANDARDS PRESCRIBED UNDER THE CANADIAN
FACTURE - CE VEHICULE EST CONFORME A TOUTES LES
SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN
TION

ATE

DE CHARGEMENT 611 KG / 1351 LB
E AVEC LES RESERVOIRS D'EAU DOUCE PLEINS
FROID 140 KG CHAUD 130 KG
FROID 308 LB CHAUD 288 LB
ET LES RESERVOIRS D'EAUX USEES VIDES
MASSE DES RESERVOIRS D'EAUX USEES PLEINS
227 KG / 501 LB



TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

THE WEIGHT OF CARGO SHOULD NEVER EXCEED 776 KG
OR 1710 LBS. LE POIDS DE CHARGEMENT NE DEVRAIT
JAMAIS EXCÉDER 776 KG OU 1710 LBS

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT AVANT	ST205/75R14D	448 KPA /65 PSI	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
REAR ARRIERE	ST205/75R14D	448 KPA /65 PSI	
SPARE DE SECOURS	ST205/75R14D	448 KPA /65 PSI	

Keystone RV Company
Oct 2021
TSCA Title VI Compliant



