

IMG_0889.jpeg



IMG_0887.jpeg



IMG_0888.jpeg







IMG_0892.jpeg





IMG_0894.jpeg





IMG_0896.jpeg



IMG_0897.jpeg











IMG_0902.jpeg





IMG_0904.jpeg





TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of the cargo should never exceed 3445 kg or 7594 lbs
Le poids du chargement ne doit jamais dépasser 3445 kg ou 7594 lbs

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
FRONT AVANT	ST225/75R15D	448 KPA / 65 PSI	
REAR ARRIERE	ST225/75R15D	448 KPA / 65 PSI	
SPARE DE SECOURS	NONE	NONE	

MANUFACTURED BY/FABRIQUE PAR: N&N REMORQUES INC. DATE: 05-2022

GVWR / PNBV 4454 KG (9819 LB)
GAWR (EACH AXLE) / PNBE (CHAQUE ESSIEU) 2227 KG (4910 LB)
TIRE/PNEU ST225/75R15D RIM/JANTE 15x6J
COLD INFL. PRESS/PRESS. DE GONFL. A FROID 448 KPA (65 PSI/LPO) SINGLE

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. - CE VEHICULE EST CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN VIGUEUR A LA DATE DE LA FABRICATION.
V.I.N./N.I.V.: 2NEB318B5NN033643 TYPE/TYPE: TRAILER/TRAITEM