



att.dN2aozPgCL1pb2iE-4Sk8C9Y8sMDE-P934JlvLEYmzc.png.jpeg





780 kg or 1720 lbs

CAUTION:
A full load of water equals 0 kg or 0 lbs of cargo @ 1 kg/L (8.33 lb/gal)

PNEU	DIMENSIONS
AVANT	ST205/75R15C
ARRIÈRE	0
DE SECOURS	ST205/75R15C

MANUFACTURED BY / FABRIQUE PAR **FOREST RIVER, Inc.** DATE **6/26/2014**

V.I.N./N.I.V. **5NHUAT219FW057158** TYPE/TYPI **TRA/REM** **TRA/REM**

GVWR/PNBV **1356 KG (2990 LB)** **ATTX612SA**

Coupler Size **2** **ATW057158**

GAWR/PNEU	TIRE/PNEU	RIMS/ANTE	COLD INFL. PRESS/PRESS DE GOMME A FROID
FRONT/AVANT 1588 KG (3500 LB)	ST205/75R15C	15 X 50J	345KPA SINGLE DUAL 50PSI/PC ☒ ☐
INTERM/INTERM 0 KG (0 LB)	0	0	0KPA SINGLE DUAL 0PSI/PC ☐ ☐
REAR/ARRIÈRE 0 KG (0 LB)	0	0	0KPA SINGLE DUAL 0PSI/PC ☐ ☐

THIS VEHICLE CONFORMS TO U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

THIS VEHICLE CONFORMS TO CANADIAN MOTOR VEHICLE SAFETY STANDARDS PRESCRIBED IN THE REGLEMENT SUR LA SECURITE DES AUTOMOBILES DU CANADA EN DATE DE SA FABRICATION.

Entrepreneur

































5FCE21E4-89E9-4404-BE6C-18ED029C196B.jpeg





D4FEA5B4-85D7-4586-9168-79D4BC3524F8.jpeg



B4913982-DC9A-4B49-9AA6-4F3E42A2FF45.jpeg



9A08CB14-7BB6-4173-B743-C38658F66060.jpeg



605581D6-21DE-4DFC-866B-12D4B950A889.jpeg



