

IMG_6146.jpeg



IMG_6147.jpeg



IMG_6148.jpeg



IMG_6149.jpeg





ELI

IMG_6155.jpeg



IMG_6156.jpeg



IMG_6157.jpeg



IMG_6158.jpeg



EUREKA



IMG_6151.jpeg



IMG_6152.jpeg



IMG_6153.jpeg



IMG_6154.jpeg



IMG_6160.jpeg



IMG_6161.jpeg



IMG_6162.jpeg







Entrepreneur

20260407_154505.jpg





Entrepreneur

20260407_154517.jpg



IMG_6163.jpeg



IMG_6164.jpeg



IMG_6165.jpeg



IMG_6167.jpeg



IMG_6168.jpeg









Entretien

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of the cargo should never exceed 1906 kg or 4201 lbs.
Le poids du chargement ne doit jamais dépasser 1906 kg ou 4201 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT AVANT	ST205/75R15	413 KPA / 60 PSI	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS FD-337
REAR ARRIERE	ST205/75R15	413 KPA / 60 PSI	
SPARE DE SECOURS	ST205/75R15	413 KPA / 60 PSI	

7PKBE1222R1001691

MANUFACTURED BY/FABRIQUE PAR: SEED CARGO DATE: 01/2024
GVWR / PNBV 2722 KG (6000 LB)
GAWR (EACH AXLE) / PNBE (CHAQUE ESSEU) 1588 KG (3500 LB)
TIRE/PNEU ST205/75R15 RIM/JANTE SILVER
COLD INFL. PRESS/PRESS. DE GONFL. A FROID 413.7 KPA (60 PSI/LCP) SINGLE
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE
CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / -CE
VEHICULE EST CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN
VIGUEUR A LA DATE DE SA FABRICATION. TYPE: TRA/REM MODEL: 6X12TA2
V.I.N.: 7PKBE1222R1001691