

IMG_7642.jpeg



IMG_7643.jpeg



IMG_7644.jpeg



IMG_7645.jpeg



IMG_7646.jpeg





IMG_7649.jpeg



IMG_7650.jpeg



IMG_7651.jpeg



IMG_7652.jpeg



IMG_7653.jpeg



IMG_7654.jpeg



IMG_7655.jpeg



IMG_7656.jpeg



IMG_7657.jpeg



IMG_7659.jpeg



IMG_7660.jpeg



IMG_7661.jpeg



IMG_7662.jpeg



IMG_7663.jpeg



IMG_7664.jpeg



IMG_7667.jpeg



IMG_7668.jpeg



IMG_7669.jpeg



IMG_7670.jpeg



IMG_7671.jpeg



IMG_7672.jpeg





IMG_7674.jpeg



IMG_7678.jpeg



IMG_7680.jpeg



IMG_7657.jpeg



IMG_7656.jpeg



IMG_7666.jpeg



IMG_7665.jpeg



IMG_7677.jpeg



IMG_7679.jpeg







IMG_7683.jpeg





Ent

MANUFACTURED BY/FABRIQUÉ PAR: Keystone RV Company DATE: 4/23/2015
 2642 Hackberry Drive
 Gosheh, IN 46526

GVWR/PNBV 7589 KG (16730 LB)
 GAWR (EACH AXLE)/PNBE(CHAQUE ESSIEU) 3175 KG (7000 LB)
 TIRE/PNEU ST235/60R16E RIMS/JANTE 16x6
 COLD INFL. PRESS/PRESS. DE GONFL. À FROID 552 KPA (80 PSIL/PC)-SINGLE

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. - CE VEHICULE EST CONFORME A TOUTES LES NORMES QUI LI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN VIGUEUR A LA DATE DE SA FABRICATION.

V.I.N./N.I.V.: 4YDF37226G4700243 TYPE/TYPE: TRAILER TRA/REM: M03720RL16

CARGO-CARRYING CAPACITY: 1611 KG
 CALCULATED WITH THE FRESH WATER TANKS FULL (COLD 204 KG HOT 45 KG.)
 AND THE WASTE WATER TANKS EMPTY
 MASS OF WASTE WATER TANKS FULL: 541 KG

CAPACITE DE CHARGEMENT: 1611 KG
 CALCULEE AVEC LES RESERVOIRS D'EAU DOUCE PLEINS (FROID 204 KG. CHAUD 45 KG.)
 ET LES RESERVOIRS D'EAUX USEES VIDES
 MASSE DES RESERVOIRS D'EAUX USEES PLEINS: 541 KG.

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed 1787 KG or 3940 LBS. Le poids de chargement ne devrait jamais exceder 1787 KG ou 3940 LBS

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT AVANT	ST235/60R16E	552 KPA /80 PSI	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
REAR ARRIERE	ST235/60R16E	552 KPA /80 PSI	
SPARE DE SECOURS	ST235/60R16E	552 KPA /80 PSI	

This vehicle contains composite wood products that comply with the applicable California Code of Regulations Section 93120.2(a) Phase 2 (P2) formaldehyde emission standards specified on the date of manufacture.





image.jpg

