

IMG_8684.jpeg



IMG_8685.jpeg



IMG_8686.jpeg



IMG_8687.jpeg



IMG_8688.jpeg



IMG_8689.jpeg



IMG_8690.jpeg



IMG_8691.jpeg



IMG_8694.jpeg



IMG_8695.jpeg





IMG_8698.jpeg



IMG_8699.jpeg







IMG_8702.jpeg



IMG_8703.jpeg



IMG_8704.jpeg



IMG_8705.jpeg



IMG_8706.jpeg



IMG_8707.jpeg



IMG_8708.jpeg



IMG_8709.jpeg





TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of the cargo should never exceed 394 kg or 870 lbs.
Le poids du chargement ne doit jamais dépasser 394 kg ou 870 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT AVANT	ST205/75R15	413 KPA / 60 PSI	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
REAR ARRIERE	ST205/75R15	413 KPA / 60 PSI	
SPARE DE SECOURS	ST205/75R15	413 KPA / 60 PSI	

7PKBE1416R1001505

MANUFACTURED BY/FABRIQUE PAR: SEED CARGO DATE: 01/2024
 GVWR / PNBV 1356 KG (2990 LB)
 GAWR (EACH AXLE) / PNBE (CHAQUE ESSIEU) 1356 KG (2990 LB)
 TIRE/PNEU ST205/75R15 RIM/JANTE SILVER
 COLD INFL. PRESS/PRESS. DE GONFL. A FROID 413.7 KPA (60 PSI/LCP) SINGLE
 THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE
 CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / -CE
 VEHICULE EST CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN
 VIGUEUR A LA DATE DE SA FABRICATION.
 V.I.N.: 7PKBE1416R1001505 TYPE: TRA/REM MODEL: 6X14SA



IMG_8692.jpeg



IMG_8693.jpeg



IMG_8712.jpeg



IMG_8713.jpeg



IMG_8714.jpeg



IMG_8715.jpeg



IMG_8716.jpeg

