

IMG\_9830.jpeg



IMG\_9831.jpeg



ELITE

IMG\_9832.jpeg



IMG\_9833.jpeg



IMG\_9834.jpeg



IMG\_9835.jpeg



IMG\_9836.jpeg



IMG\_9837.jpeg



IMG\_9838.jpeg



IMG\_9839.jpeg



IMG\_9840.jpeg



IMG\_9841.jpeg



IMG\_9842.jpeg



IMG\_9843.jpeg



IMG\_9844.jpeg



IMG\_9845.jpeg



IMG\_9846.jpeg





IMG\_9848.jpeg



IMG\_9849.jpeg





IMG\_9851.jpeg



IMG\_9852.jpeg



IMG\_9853.jpeg



# 547-5050

**TIRE AND LOADING INFORMATION**  
**RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT**

The weight of the cargo should never exceed 2375 kg or 5236 lbs.  
 Le poids du chargement ne doit jamais dépasser 2375 kg ou 5236 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT AVANT	ST205/75R15	413 KPA / 60 PSI	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS FD-337
REAR ARRIERE	ST205/75R15	413 KPA / 60 PSI	
SPARE DE SECOURS	ST205/75R15	413 KPA / 60 PSI	

7PKBE1423T1000764

MANUFACTURED BY/FABRIQUE PAR: SEED CARGO  
 DATE: 08/2025  
 GVWR / PNBV 3175 KG (7000 LB)  
 GAWR (EACH AXLE) / PNBE (CHAQUE ESSIEU) 1588 KG (3500 LB)  
 TIRE/PNEU ST205/75R15 RIM/JANTE SILVER  
 COLD INFL. PRESS/PRESS. DE GONFL. A FROID 413.7 KPA (60 PSI/LCP) SINGLE  
 THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE  
 CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / -CE  
 VEHICULE EST CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN  
 VIGUEUR A LA DATE DE SA FABRICATION.  
 V.I.N.: 7PKBE1423T1000764 TYPE: TRA/REM MODEL: 7x14TA2

EntrepreCK