

image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



Entrepreneur

image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



EntrepeX



TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

SEATING CAPACITY NOMBRE DE PLACES	TOTAL 5	FRONT AVANT	REAR ARRIERE
The combined weight of occupants and cargo should never exceed Le poids total des occupants et de la cargaison ne doit jamais dépasser		500 kg or 1100 lb.	
TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DES USAGERS POUR PLUS DE RENSEIGNEMENTS
FRONT AVANT	205/55R16	259kPa, 34psi	95N
REAR ARRIERE	205/55R16	219kPa, 31psi	
SPARE DE SECOURS	112S/80D15	429kPa, 60psi	

MANUFACTURED IN KOREA BY
HYUNDAI MOTOR COMPANY

OCT/23/20

GVWR/PNBV 1750 kg
GAWR/PNBE FRONT 1030 kg
GAWR/PNBE REAR 950 kg

PAINT WAWTRIM NNB

V.I.N. KMHLM4AGXMU086979
TYPE: PC/VT ICES/NMB-002

CVSS • CANADA • NS/AC
A54
TRANSPORT

image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



image.jpg



Entrepreneur