

20260526_083935.jpg



















20260526_084026.jpg



20260526_084030.jpg



20260526_084038.jpg




20260526_084046.jpg



20260526_084051.jpg



THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.
THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. - CE VEHICULE EST
CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN VIGUEUR A LA DATE DE SA FABRICATION.
V.I.N. / N.I.V.: **1S9BL162XPW873994** TYPE / TYPE: TRAILER TRA / REM **64160RANCHER-BP** FD-306 REV. A

 **TIRE AND LOADING INFORMATION**

The weight of cargo should never exceed
1814 Kg or 4000 Lbs.


TIRE	SIZE	COLD TIRE PRESSURE
FRONT	ST225-75R X 15	450 kpa/65 psi
REAR	ST225-75R X 15	450 kpa/65 psi
SPARE	ST225-75R X 15	450 kpa/65 psi

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FD-314

Entire



MANUFACTURED BY / FABRIQUE PAR: **SHADOW TRAILERS, LLC.** DATE **03/23**
GVWR / PNBV **3029 KG (6680 LB)**
GAWR (EACH AXLE) / PNBE (CHAQUE ESSIEU) **1587 KG (3500 LB)** TIRES / PNEU **ST225/75R 15**
RIMS / JANTE **15 X 6.0 J**
COLD INFL. PRESS. / PRESS. DE GONFL. A FROID **450 KPA (65 PSI / LPC)** SINGLE DUAL
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.
THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. - CE VEHICULE EST CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICULES AUTOMOBILES DU CANADA EN VIGUEUR A LA DATE DE SA FABRICATION.
V.I.N. / N.I.V.: **1S9BL162XPW873994** TYPE / TYPE: TRAILER TRA / REM **64160RANCHER-BP** FD-306 REV A



TIRE AND LOADING INFORMATION
The weight of cargo should never exceed
1814 Kg or 4000 Lbs

TIRE	SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT	ST225-75R X 15	450 kpa/65 psi	
REAR	ST225-75R X 15	450 kpa/65 psi	
SPARE	ST225-75R X 15	450 kpa/65 psi	

FD-314

WELD
ASSEMB

20260526_084126.jpg



20260526_084128.jpg



20260526_084131.jpg



20260526_084141.jpg



20260526_084155.jpg

